

BOSTITCH F33PT-E

BOSTITCH F33PT-E Stick Nailer

33° Stick Nailer 90mm Max. Uses Paper & wire weld collated Nails.

- Magnesium Housing.
- Push Button Depth Control.
- Ideal for construction .
- Carry Case .
- Sequential Trip.

FEATURES

- Sequential Trip
- No Mar Tip
- Magnesium Housing
- Compact Nose
- Non Slip Serrated Tip
- Rubber Comfort Grip
- 33° Magazine
- Carry Case

SPECIFICATIONS

Model	F33PT-E
Weight	3.6Kg
Dimensions LxWxH	457 x 133 x 355 mm
Head Diameter	6.8-7.2 mm
Length (mm)	50 (min) - 90 (max)
Wire Diameter (mm)	2.5 (min) 3.3 (max)
Magazine Capacity	75 Nails (max)
Depth Control	YES Push Button
Power Type	Pneumatic
Input Thread	1/4 BSP
Operating Pressure	70-120 psi 4.8-8.3 BAR
Air Consumption	2.47 litre Per Shot
Noise LPA 1sd	83.9
Noise LWA 1sd	90.70
Noise LPA 1s, 1m	77.70
Vibration/ Uncertainty	2.47 / N/A m/s2
Collation	33° paper 33° wire weld
Options	Contact Trip trigger Carry Case

